



AKIS LED - 15 - CCT

220V 240V	IP20 IP44	IK08		ECODESIGN COMPLIANT	CE	RoHS	Ta -20° +45°C
--------------	--------------	------	--	------------------------	----	------	------------------

Item.: CE0215MW-TW (version on-off)

Item.: CE0215MW-TW (version TRIAC dim.)

Recessed downlight LED, 220-240Vac, 15W,
2700/4000/6000K, CRI>80, White Reflector - Standard 36° Optics



Description

Available in two versions, for ceiling and track installation.
Adjustable head, 90° on the vertical axis and 320° on the horizontal one.
Die-cast aluminum body.
Powder coating anti-yellowing stabilized against UV rays.
Reflectors in metallized PC.
Compliant: EN 60598-1 and EN 60598-2-2.

Light source

COB LED with nominal efficiency up to 135 lumens/Watt.
Nominal flux: 1620 lm.
White color temperature: 2700/4000/6000K
Color rendering index: CRI>80.
Lifetime: >50000h with L70.
Number of light sources: 1.
Output flux of the equipment: 1350-1550 lm.

Electrical data

Driver power supply: input 220-240 Vac.
Average system power consumption: 15W.
Driver protections: Thermal, short circuit, overvoltage.
Driver connection: whit Internal terminal block.
Insulation class: II.
Functions: On-Off / TRIAC dim.

Technical Description

Frame finish: White.
Lamp protection: IP44.
Driver protection: IP20.
Mechanical resistance: IK08.
Quality marks: CE, RoHS..

Installation

Ceiling or electrified track installation.
Painted metal fixing base.
These devices are designed for modern control systems.
For different options, see the "Light Control" section.

Dimensions

Ø100 x H.108mm

Standard:

Quality marks: CE RoHS
Standards: CEI EN 60598-1; CEI EN 60598-2-03.
2014/30/EU, 2014/35/EU; ELR Ecodesign 2019/2015

ACCESSORIES



cod. REF015-G
(G) Shiny gold reflector



cod. LEN012-N
(N) Lents20°



cod. SUS001
Suspension cable



AKIS LED - 15 - CCT

220V 240V	IP20 IP44	IK08		ECODESIGN COMPLIANT	CE	RoHS	Ta -20° +45°C
--------------	--------------	------	--	------------------------	----	------	------------------

Item.: **CE0215MB-TW** (version on-off)

Item.: **CED0215MB-TW** (version TRIAC dim.)

Recessed downlight LED, 220-240Vac, 15W,
2700/4000/6000K, CRI>80, Black Reflector - Standard 36° Optics



Description

Available in two versions, for ceiling and track installation.
Adjustable head, 90° on the vertical axis and 320° on the horizontal one.
Die-cast aluminum body.
Powder coating anti-yellowing stabilized against UV rays.
Reflectors in metallized PC.
Compliant: EN 60598-1 and EN 60598-2-2.

Light source

COB LED with nominal efficiency up to 135 lumens/Watt.
Nominal flux: 1620 lm.
White color temperature: 2700/4000/6000K
Color rendering index: CRI>80.
Lifetime: >50000h with L70.
Number of light sources: 1.
Output flux of the equipment: 1350-1550 lm.

Electrical data

Driver power supply: input 220-240 Vac.
Average system power consumption: 15W.
Driver protections: Thermal, short circuit, overvoltage.
Driver connection: whit Internal terminal block.
Insulation class: II.
Functions: On-Off / TRIAC dim.

Technical Description

Frame finish: Black.
Lamp protection: IP44.
Driver protection: IP20.
Mechanical resistance: IK08.
Quality marks: CE, RoHS..

Installation

Ceiling or electrified track installation.
Painted metal fixing base.
These devices are designed for modern control systems.
For different options, see the "Light Control" section.

Dimensions

Ø100 x H.108mm

Standard:

Quality marks: CE RoHS
Standards: CEI EN 60598-1; CEI EN 60598-2-03.
2014/30/EU, 2014/35/EU; ELR Ecodesign 2019/2015

ACCESSORIES



cod. REF015-G
(G) Shiny gold reflector



cod. LEN012-N
(N) Lents20°



cod. SUS001
Suspension cable