



AX LED

| | | | | | | | |
|--------------|------|------|--|------------------------|----|------|------------------|
| 220V 240V | IP65 | IK08 | | ECODESIGN COMPLIANT | CE | RoHS | Ta -40° +45°C |
|--------------|------|------|--|------------------------|----|------|------------------|

Item.: WLO2H10-830

Wall lamp with double light beam Up&Down

220-240Vac, 10W, double counter-emission, 3000K, CRI>80,



☐ Body color white

Product Description

AX LED IP65 is a wall mounted lamp with opposite light beams and adjustable in width as desired. Body entirely in white painted aluminum, glass diffuser. High impact resistance. Optical system adjustable in both directions to obtain light beams of different aperture as desired.

Fixing via steel bracket. IP65 protection rating makes it ideal for both outdoor and indoor installations.

Body in white painted aluminum.

LED protection diffuser in anti-reflective and anti-glare glass.

EN 60598-1 and EN 60598-2-2.

Source

Double SMD single beam LED module

Energy class of the source E

LED light output: 150 lm/W

Useful luminous flux 1450 lm, CCT 3000K

Power .in ON mode: 10W

Selection: <6 SDCM.

Asymmetrical beam angle diplo for wall and front area lighting.

Driver

Integrated electronic driver

Installation

Wall / Ceiling using the supplied fixing bracket

Dimensions

110 x 120 x H.110mm

IP65

Technical data

function: on-off

Insulation class: I

Power supply: 220-240V 50/60Hz

Total absorption: 10W

PF: ≥0.90

Ta: -20°...+45°C

Number of integrated LED modules: 2

Useful luminous flux: 1450 lm (3000K)

CRI: >80

IP65 - IK08

Reference regulations

EN 60598-1 e EN 60598-2-1.

EMC 2014/30/UE and

LVD 2014/35/UE

