

ETT LED Asymmetric

230V	IP67	IK10		ECODESIGN COMPLIANT	CE RoHS	Ta -40° +45°C
------	------	------	--	------------------------	---------	------------------



Item.: IG02H03A-830

LED recessed IP67, 220-240Vac, 3000K,
CRI>80, 3.1W, on-off, asymmetric 45°



 Satin steel

IP67



Product description

ETT LED is a drive-over LED recessed light with asymmetric 45°x35° optics. Head in satin stainless steel (SUS 316#) and body in anodized and powder-coated aluminum. Suitable for indoor and outdoor installations. Thanks to the steel springs integrated into the body, direct installation is also possible in false ceilings, false walls and steps. The package includes the outer casing for masonry.

Cable with water stop system that guarantees the seal against infiltrations.

Source

Light source: Osram LED.
Energy class: E (Ecodesign ELR 2019/2015)
Color temperature: 3000K
LED light output: 150 lm/W
Chromatic color index: CRI>80
Lumen maintenance: L80 B10 60000 h
Luminous efficiency of the device (LOR): 128.12 lm/W
Lumen output: 156 lm
Photobiological risk class: "0" Exempt

Electrical installation data

Power supply: 230V
Absorption: 3.1W
Cable: 3x0.75 sqm
Insulation class: I
Functions: on-off

Structural data

Front: stainless steel with
Optical system: 1 power LED placed inside the optical compartment, optical lens
in thermostable methacrylate on the LED, ultra-transparent tempered glass stabilized to UV rays. Body in die-cast aluminum anodized and painted against corrosion.
Built-in plastic sleeve included.
Protection: IP67
Resistance to mechanical impacts: IK10
Quality marks: CE RoHS (for all components)
Reference Standards: CEI EN 60598-1; CEI EN 60598-2-03.

Standards

IEC EN 60598-1:2015 + A11:2009. IEC 60598-2:2015 2-1
Photobiological risk: RISK GROUP 0 Device certified RISK GROUP 0 (exempt)
The device does not present any hazards due to normal behavioral limitations to exposure - in accordance with
CEI EN 62471:2010-01, IEC TR 62778:2014.

ACCESSORIES



cod. CON3P66-M
Male connector
IP68 3 poly

cod. CON5P66-M
Male connector
IP68 5 poly

cod. CON3P66-F
Female connector
IP68 3 poly

cod. CON5P66-F
Female Connector
IP68 5 poly

