



LYS LED - 60X60

220V 240V	IP44 IP54	IK06		ECODESIGN COMPLIANT	CE	RoHS	Ta -20° +45°C
--------------	--------------	------	--	------------------------	----	------	------------------

Item: LPN-16P640-840

Recessed On-Off downlight LED, 220-240Vac, 40W,
4000K, CRI>80, Smooth anti-glare diffuser



Description

Die-cast aluminum body.
Powder coating anti-yellowing stabilized against UV rays.
Interchangeable power supply
Flicker free
Compliant: EN 60598-1 and EN 60598-2-2.

Light source

SMD LED with nominal efficiency up to 135 lumens/Watt.
Nominal flux: 6120 lm.
White color temperature: 4000 K. (on request 3000K, 5000K)
Color rendering index: CRI>80
Lifetime: >50000h with L70.
Number of light sources: 1.
Output flux of the equipment: 3600 lm.

Electrical data

Driver power supply: input 220-240 Vac.
Average system power consumption: 40W.
Driver protections: Thermal, short circuit, overvoltage.
Driver connection: whit Internal terminal block.
Insulation class: II.
Functions: On-Off

Technical Description

Frame finish: White.
Lamp protection: IP54.
Driver protection: IP44.
Mechanical resistance: IK06.
Quality marks: CE, RoHS.

Installation

Ceiling mounted frame.
Fixing with suspension kit
These devices are designed for modern control systems.
For different options, see the "Light Control" section.


Dimensioni

40W =595X955X36.5

Standard:

Quality marks: CE RoHS
Standards: CEI EN 60598-1; CEI EN 60598-2-03.
2014/30/EU, 2014/35/EU; ELR Ecodesign 2019/2015

ACCESSORIES



cod. KEM-90E

Emergency kit for LED equipment
complete with battery for 3 hours.