


WD - 25 LED 25W-40°-IP65




| | | | | | | | |
|--------------|--------------|------|--|------------------------|----|------|------------------|
| 220V 240V | IP20 IP44 | IK08 | | ECODESIGN COMPLIANT | CE | RoHS | Ta -20° +45°C |
|--------------|--------------|------|--|------------------------|----|------|------------------|

Item.: RC0125S-930

Recessed On-Off downlight LED, 220-240Vac, 25W,
3000K, CRI92, Standard 60°- Glossy silver reflector



Foro per
incasso: Ø120 mm



Description

IP65 ceiling recessed
Die-cast aluminum body.
Powder coating anti-yellowing stabilized against UV rays.
Reflectors in metallized PC.
Upper LED frosted screen in PC.
Compliant: EN 60598-1 and EN 60598-2-2.

Light source

COB LED with nominal efficiency up to 135 lumens/Watt.
Nominal flux: 3375 lm.
White color temperature: 3000 K.
Color rendering index: CRI92.
Lifetime: >50000h with L70.
Number of light sources: 1.
Output flux of the equipment: 2504 lm.

Electrical data

Driver power supply: input 220-240 Vac.
Average system power consumption: 25W.
Driver protections: Thermal, short circuit, overvoltage.
Driver connection: whit Internal terminal block.
Insulation class: II.
Functions: On-Off.

Technical Description

Frame finish: White.
Lamp protection: IP65.
Driver protection: IP65.
Mechanical resistance: IK08.
Quality marks: CE, RoHS..

Installation

Recessed installation.
Fixing by steel springs.
These devices are designed for modern control systems.
For different options, see the "Light Control" section.

Dimensions

25W: 130 x H.78mm, foro Ø120mm

Standard:

Quality marks: CE RoHS
Standards: CEI EN 60598-1; CEI EN 60598-2-03.
2014/30/EU, 2014/35/EU; ELR Ecodesign 2019/2015