


# WD - 25 LED 25W-40°-IP65




220V 240V	IP20 IP44	IK08		ECODESIGN COMPLIANT	CE	RoHS	Ta -20° +45°C
--------------	--------------	------	--	------------------------	----	------	------------------

## Item.: RC0125B-940

Recessed On-Off downlight LED, 220-240Vac, 25W,  
4000K, CRI92, Standard 60°- Black reflector



Foro per  
incasso: Ø120 mm



### Description

IP65 ceiling recessed  
Die-cast aluminum body.  
Powder coating anti-yellowing stabilized against UV rays.  
Reflectors in metallized PC.  
Upper LED frosted screen in PC.  
Compliant: EN 60598-1 and EN 60598-2-2.

### Light source

COB LED with nominal efficiency up to 135 lumens/Watt.  
Nominal flux: 3375 lm.  
White color temperature: 4000 K.  
Color rendering index: CRI92.  
Lifetime: >50000h with L70.  
Number of light sources: 1.  
Output flux of the equipment: 2538 lm.

### Electrical data

Driver power supply: input 220-240 Vac.  
Average system power consumption: 25W.  
Driver protections: Thermal, short circuit, overvoltage.  
Driver connection: whit Internal terminal block.  
Insulation class: II.  
Functions: On-Off.

### Technical Description

Frame finish: White.  
Lamp protection: IP65.  
Driver protection: IP65.  
Mechanical resistance: IK08.  
Quality marks: CE, RoHS..

### Installation

Recessed installation.  
Fixing by steel springs.  
These devices are designed for modern control systems.  
For different options, see the "Light Control" section.

### Dimensions

25W: 130 x H.78mm, foro Ø120mm

### Standard:

Quality marks: CE RoHS  
Standards: CEI EN 60598-1; CEI EN 60598-2-03.  
2014/30/EU, 2014/35/EU; ELR Ecodesign 2019/2015