



Professional Aluminium LED Profile

S55 DOUBLE

ceiling and wall surface suspension



INSTALLATION
surface




DISSIPATION
MAXIMUM
60 W/m




TAILOR MADE
cutting service
strip installed
accessories and cable

S55 Double is an aluminium modular system with linear elements that can be connected to each other and installed in suspended, surface-mounted or wall-mounted. Two or one light outlet as desired, two different diffuser models for the lower light, microprismatic (UGR<19) or opal diffusing. Available in versions standard with silver or white anodised body while black and corten colours are only available on request. Possibility of customised profiles complete with single or double LED strip inside inside, power cable and accessories for suspension or surface mounting.



THE STANDARD PACKAGE INCLUDES:

- 1 aluminium profile L.2 m
- 1 diffuser L.2 m



cod.	colour	length standard	lowspeak lower	lowspeak upper
PA7055G-P	silver	2 mt	prismatizzato	opal
PA7055G-O	silver	2 mt	opal	opal
cod.	colour	length standard	lowspeak lower	lowspeak upper
PA7055W-P	white	2 mt	prismatizzato	opal
PA7055W-O	white	2 mt	opal	opal


ACCESSORIES



cod. PAG3535
linear joint



cod. PAC7055
fixing clips
to wall



cod. PAT7055-G (Grey)
cod. PAT7055-W (White)
blind end cap



cod. PAG3535-90
90° flat joint



PAS7055
Suspension kit
including 2 cables and
4 supports



cod. PAG3535-90V
vertical 90° joint°



ST00052415-9xx
Linya COB Strip CRI>90
24Vdc - 15W/m - 480 LED/m - IP20



ST1A052422-9xx
Linya SMD Strip CRI>90
24Vdc - 22W/m - 238 LED/m - IP20

