



## CADY-LED 30 RGBW



cod.: BL030L12DXA-RGBW

Asymmetrical LED BAR RGBW, 30 cm length, 24Vac, 12W,  
Asymmetrical Distribution light 10°x60°, DMX control



### Product description

CADY-LED 30 is an linear wallwasher, 10°x 60° beam angle, L.300 mm. Flexible installation method, surface installation, recessed slot installation and ceiling installation.

Product light-emitting surface made of Mitsubishi Acrylic double-color mixed material, solid three-dimensional light, soft and uniform light effect.

Standard cable of this product is IP67 one IN and one OUT with waterproof connector.

RGBW light, DMX512 control.

6063 Aluminum alloy lamp body, stamping aluminum alloy end cap, stainless steel fasteners.

CE certification and qualified inspections by National Lighting Quality Supervision and Inspection Center.

### Light source data

Light source: RGBW 4in1

Light source energy class white LED: E (Ecodesign ELR 2019/2015)

Color rendering index: CRI>90

Flow maintenance: L80 B10 60000 h

Number of sources: 8 (RGBW 4in1)

Lumens: 676 lm

Luminous efficiency (LOR) for white LED: 110.6 lm/W

Photobiological risk class: "0" Exempt

### Electrical data

Power supply: 230Vac

Total system absorption: 12W

Connection: Cable with connector

Insulation class: I

Control by DMX signal with RDM functions

Effects: RGBW mixing color

### Mechanical data

Luminaire colour: Grey

Optical system: 8 LED RGBW 4in1 placed inside the optical compartment, thermostable methacrylate optical lenses on each LED, ultra-transparent UV-rays stabilized tempered glass. Resin-coated optical container for protection from sand and humidity.

Body in anodized aluminum and painted against corrosion.

Adjustable stainless steel brackets.

Protection: IP66

Power connectors: IP67

Mechanical impact resistance: IK08

Quality marks: CE RhOS (for all components)

### Classifications and Norms

STANDARDS: CEI EN 60598-1, EN 62471, 2009/125/CE, 874/2012/CE, 2014/30/EU, 2014/35/EU, CEI EN 60598-2-2.

Current Ecodesign Directive

### OPTIONAL ACCESSORIES



**cod. PHLG-320-24**

IP67 Power supply  
320W - 24Vdc



**cod. ESPW-T5P**

5 PINS T-Connector



**cod. ESN-1M5P**

Male & Female  
5pins type connector  
with 1m cable



**cod. ESPW-03F5P**

Female connector  
with 350mm cable



**cod. EL-DMX-2048**

PC Interface (for DIN rail)  
DMX Programmable controller  
4 U-DMX, Master/Slave Mode  
Ethernet, Smart Contact,  
infrared, Time clock