


SGL LED - 12W

220V 240V	IP20 IP44	IK08		ECODESIGN COMPLIANT	CE RoHS	Ta -20° +45°C
--------------	--------------	------	--	------------------------	---------	------------------



Item.: **RC0512LB-927** (version on-off)

Item.: **RC0512LB-927** (version DALI)

Recessed downlightLED, 220-240Vac, 12W,
2700K, CRI92, Standard 60°- Black reflector



Foro per
incasso: Ø75 mm



Description

modular ceiling recessed system
Die-cast aluminum body.
Powder coating anti-yellowing stabilized against UV rays.
Reflectors in metallized PC.
Upper LED frosted screen in PC.
Compliant: EN 60598-1 and EN 60598-2-2.

Light source

COB LED with nominal efficiency up to 135 lumens/Watt.
Nominal flux: 1620 lm.
White color temperature: 2700 K.
Color rendering index: CRI92.
Lifetime: >50000h with L70.
Number of light sources: 1.
Output flux of the equipment: 1526 lm.

Electrical data

Driver power supply: input 220-240 Vac.
Average system power consumption: 12W.
Driver protections: Thermal, short circuit, overvoltage.
Driver connection: whit Internal terminal block.
Insulation class: II.
Functions: On-Off / DALI

Technical Description

Frame finish: Black.
Lamp protection: IP44.
Driver protection: IP20.
Mechanical resistance: IK08.
Quality marks: CE, RoHS..

Installation

Recessed installation.
Fixing by steel springs.
These devices are designed for modern control systems.
For different options, see the "Light Control" section.

Dimensions

Ø88x 88 x H.85mm, hole Ø75mm..

Standard:

Quality marks: CE RoHS
Standards: CEI EN 60598-1; CEI EN 60598-2-03.
2014/30/EU, 2014/35/EU; ELR Ecodesign 2019/2015

ACCESSORIES



cod. REF012-S
(S) Shiny silver reflector




cod. REF012-G
(G) Shiny gold reflector



cod. LEN012-S
(S) 24° lens



cod. LEN012-L
(L) 60° lens




cod. KEM-90E
Emergency kit for LED equipment
complete with battery for 3 hours duration.



SGL LED - 12W

220V 240V	IP20 IP44	IK08		ECODESIGN COMPLIANT	CE RoHS	Ta -20° +45°C
--------------	--------------	------	--	------------------------	---------	------------------

Item.: **RC0512LB-930** (version on-off)
Item.: **RCD0512LB-930** (version DALI)
Recessed downlight LED, 220-240Vac, 12W,
3000K, CRI92, Standard 60°- Black reflector



Foro per
incasso: Ø75 mm



Description

modular ceiling recessed system
Die-cast aluminum body.
Powder coating anti-yellowing stabilized against UV rays.
Reflectors in metallized PC.
Upper LED frosted screen in PC.
Compliant: EN 60598-1 and EN 60598-2-2.

Light source

COB LED with nominal efficiency up to 135 lumens/Watt.
Nominal flux: 1620 lm.
White color temperature: 3000 K.
Color rendering index: CRI92.
Lifetime: >50000h with L70.
Number of light sources: 1.
Output flux of the equipment: 1590 lm.

Electrical data

Driver power supply: input 220-240 Vac.
Average system power consumption: 12W.
Driver protections: Thermal, short circuit, overvoltage.
Driver connection: whit Internal terminal block.
Insulation class: II.
Functions: On-Off / DALI

Technical Description

Frame finish: Black.
Lamp protection: IP44.
Driver protection: IP20.
Mechanical resistance: IK08.
Quality marks: CE, RoHS..

Installation

Recessed installation.
Fixing by steel springs.
These devices are designed for modern control systems.
For different options, see the "Light Control" section.

Dimensions

Ø88x 88 x H.85mm, hole Ø75mm..

Standard:

Quality marks: CE RoHS
Standards: CEI EN 60598-1; CEI EN 60598-2-03.
2014/30/EU, 2014/35/EU; ELR Ecodesign 2019/2015

ACCESSORIES



cod. REF012-S
(S) Shiny silver reflector




cod. REF012-G
(G) Shiny gold reflector



cod. LEN012-S
(S) 24° lens



cod. LEN012-L
(L) 60° lens



cod. KEM-90E
Emergency kit for LED equipment
complete with battery for 3 hours duration.


SGL LED - 12W

220V 240V	IP20 IP44	IK08		ECODESIGN COMPLIANT	CE RoHS	Ta -20° +45°C
--------------	--------------	------	--	------------------------	---------	------------------



Item.: RC0512LB-940 (version on-off)

Item.: RC0512LB-940 (version DALI)

Recessed downlight LED, 220-240Vac, 12W,
4000K, CRI92, Standard 60°- Black reflector



Foro per
incasso: Ø75 mm



Description

modular ceiling recessed system
Die-cast aluminum body.
Powder coating anti-yellowing stabilized against UV rays.
Reflectors in metallized PC.
Upper LED frosted screen in PC.
Compliant: EN 60598-1 and EN 60598-2-2.

Light source

COB LED with nominal efficiency up to 135 lumens/Watt.
Nominal flux: 1620 lm.
White color temperature: 4000 K.
Color rendering index: CRI92.
Lifetime: >50000h with L70.
Number of light sources: 1.
Output flux of the equipment: 1611 lm.

Electrical data

Driver power supply: input 220-240 Vac.
Average system power consumption: 12W.
Driver protections: Thermal, short circuit, overvoltage.
Driver connection: whit Internal terminal block.
Insulation class: II.
Functions: On-Off / DALI

Technical Description

Frame finish: Black.
Lamp protection: IP44.
Driver protection: IP20.
Mechanical resistance: IK08.
Quality marks: CE, RoHS..

Installation

Recessed installation.
Fixing by steel springs.
These devices are designed for modern control systems.
For different options, see the "Light Control" section.

Dimensions

Ø88x 88 x H.85mm, hole Ø75mm..

Standard:

Quality marks: CE RoHS
Standards: CEI EN 60598-1; CEI EN 60598-2-03.
2014/30/EU, 2014/35/EU; ELR Ecodesign 2019/2015

ACCESSORIES



cod. REF012-S
(S) Shiny silver reflector




cod. REF012-G
(G) Shiny gold reflector



cod. LEN012-S
(S) 24° lens



cod. LEN012-L
(L) 60° lens




cod. KEM-90E
Emergency kit for LED equipment
complete with battery for 3 hours duration.



SGL LED - 12W

220V 240V	IP20 IP44	IK08		ECODESIGN COMPLIANT	CE RoHS	Ta -20° +45°C
--------------	--------------	------	--	------------------------	---------	------------------

cod.: **RC0512LW-927** (version on-off)
 cod.: **RCD0512LW-927** (version DALI)
 Recessed downlight LED, 220-240Vac, 12W,
 2700K, CRI92, Standard 60° - White reflector



Foro per
incasso: Ø75 mm



Description

modular ceiling recessed system
 Die-cast aluminum body.
 Powder coating anti-yellowing stabilized against UV rays.
 Reflectors in metallized PC.
 Upper LED frosted screen in PC.
 Compliant: EN 60598-1 and EN 60598-2-2.

Light source

COB LED with nominal efficiency up to 135 lumens/Watt.
 Nominal flux: 1620 lm.
 White color temperature: 2700 K.
 Color rendering index: CRI92.
 Lifetime: >50000h with L70.
 Number of light sources: 1.
 Output flux of the equipment: 1526 lm.

Electrical data

Driver power supply: input 220-240 Vac.
 Average system power consumption: 12W.
 Driver protections: Thermal, short circuit, overvoltage.
 Driver connection: whit Internal terminal block.
 Insulation class: II.
 Functions: On-Off / DALI

Technical Description

Frame finish: White.
 Lamp protection: IP44.
 Driver protection: IP20.
 Mechanical resistance: IK08.
 Quality marks: CE, RoHS..

Installation

Recessed installation.
 Fixing by steel springs.
 These devices are designed for modern control systems.
 For different options, see the "Light Control" section.

Dimensions

Ø88x 88 x H.85mm, hole Ø75mm..

Standard:

Quality marks: CE RoHS
 Standards: CEI EN 60598-1; CEI EN 60598-2-03.
 2014/30/EU, 2014/35/EU; ELR Ecodesign 2019/2015

ACCESSORIES



cod. REF012-S
(S) Shiny silver reflector




cod. REF012-G
(G) Shiny gold reflector



cod. LEN012-S
(S) 24° lens



cod. LEN012-L
(L) 60° lens



cod. KEM-90E
Emergency kit for LED equipment
complete with battery for 3 hours duration.


SGL LED - 12W

220V 240V	IP20 IP44	IK08		ECODESIGN COMPLIANT	CE RoHS	Ta -20° +45°C
--------------	--------------	------	--	------------------------	---------	------------------



Item.: **RC0512LW-930** (version on-off)

Item.: **RCD0512LW-930** (version DALI)

Recessed downlight LED, 220-240Vac, 12W,
3000K, CRI92, Standard 60°- White reflector



Foro per
incasso: Ø75 mm



Description

modular ceiling recessed system
Die-cast aluminum body.
Powder coating anti-yellowing stabilized against UV rays.
Reflectors in metallized PC.
Upper LED frosted screen in PC.
Compliant: EN 60598-1 and EN 60598-2-2.

Light source

COB LED with nominal efficiency up to 135 lumens/Watt.
Nominal flux: 1620 lm.
White color temperature: 3000 K.
Color rendering index: CRI92.
Lifetime: >50000h with L70.
Number of light sources: 1.
Output flux of the equipment: 1590 lm.

Electrical data

Driver power supply: input 220-240 Vac.
Average system power consumption: 12W.
Driver protections: Thermal, short circuit, overvoltage.
Driver connection: whit Internal terminal block.
Insulation class: II.
Functions: On-Off / DALI

Technical Description

Frame finish: White.
Lamp protection: IP44.
Driver protection: IP20.
Mechanical resistance: IK08.
Quality marks: CE, RoHS..

Installation

Recessed installation.
Fixing by steel springs.
These devices are designed for modern control systems.
For different options, see the "Light Control" section.

Dimensions

Ø88x 88 x H.85mm, hole Ø75mm..

Standard:

Quality marks: CE RoHS
Standards: CEI EN 60598-1; CEI EN 60598-2-03.
2014/30/EU, 2014/35/EU; ELR Ecodesign 2019/2015

ACCESSORIES



cod. REF012-S
(S) Shiny silver reflector




cod. REF012-G
(G) Shiny gold reflector



cod. LEN012-S
(S) 24° lens



cod. LEN012-L
(L) 60° lens




cod. KEM-90E
Emergency kit for LED equipment
complete with battery for 3 hours duration.

SGL LED - 12W



220V 240V	IP20 IP44	IK08		ECODESIGN COMPLIANT	CE RoHS	Ta -20° +45°C
--------------	--------------	------	--	------------------------	---------	------------------

Item.: **RC0512LW-940** (version on-off)
Item.: **RCD0512LW-940** (version DALI)

Recessed downlight LED, 220-240Vac, 12W,
4000K, CRI92, Standard 60°- White reflector



Foro per
incasso: Ø75 mm



Description

modular ceiling recessed system
Die-cast aluminum body.
Powder coating anti-yellowing stabilized against UV rays.
Reflectors in metallized PC.
Upper LED frosted screen in PC.
Compliant: EN 60598-1 and EN 60598-2-2.

Light source

COB LED with nominal efficiency up to 135 lumens/Watt.
Nominal flux: 1620 lm.
White color temperature: 4000 K.
Color rendering index: CRI92.
Lifetime: >50000h with L70.
Number of light sources: 1.
Output flux of the equipment: 1611 lm.

Electrical data

Driver power supply: input 220-240 Vac.
Average system power consumption: 12W.
Driver protections: Thermal, short circuit, overvoltage.
Driver connection: whit Internal terminal block.
Insulation class: II.
Functions: On-Off / DALI

Technical Description

Frame finish: White.
Lamp protection: IP44.
Driver protection: IP20.
Mechanical resistance: IK08.
Quality marks: CE, RoHS..

Installation

Recessed installation.
Fixing by steel springs.
These devices are designed for modern control systems.
For different options, see the "Light Control" section.

Dimensions

Ø88x 88 x H.85mm, hole Ø75mm..

Standard:

Quality marks: CE RoHS
Standards: CEI EN 60598-1; CEI EN 60598-2-03.
2014/30/EU, 2014/35/EU; ELR Ecodesign 2019/2015

ACCESSORIES



cod. REF012-S
(S) Shiny silver reflector




cod. REF012-G
(G) Shiny gold reflector



cod. LEN012-S
(S) 24° lens



cod. LEN012-L
(L) 60° lens



cod. KEM-90E
Emergency kit for LED equipment
complete with battery for 3 hours duration.