


# SGL LED - 20W



220V 240V	IP20 IP44	IK08		ECODESIGN COMPLIANT	CE RoHS	Ta -20° +45°C
--------------	--------------	------	--	------------------------	---------	------------------

## Item.: RCD0520LB-940

Recessed DALI downlightLED, 220-240Vac, 20W,  
4000K, CRI92, Standard 60°- Black reflector



Foro per  
incasso: Ø95 mm



### Description

modular ceiling recessed system  
Die-cast aluminum body.  
Powder coating anti-yellowing stabilized against UV rays.  
Reflectors in metallized PC.  
Upper LED frosted screen in PC.  
Compliant: EN 60598-1 and EN 60598-2-2.

### Light source

COB LED with nominal efficiency up to 135 lumens/Watt.  
Nominal flux: 2700lm.  
White color temperature: 4000 K.  
Color rendering index: CRI92.  
Lifetime: >50000h with L70.  
Number of light sources: 1.  
Output flux of the equipment: 2221 lm.

### Electrical data

Driver power supply: input 220-240 Vac.  
Average system power consumption: 20W.  
Driver protections: Thermal, short circuit, overvoltage.  
Driver connection: whit Internal terminal block.  
Insulation class: II.  
Functions: DALI.

### Technical Description

Frame finish: white.  
Lamp protection: IP44.  
Driver protection: IP20.  
Mechanical resistance: IK08.  
Quality marks: CE, RoHS..

### Installation

Recessed installation.  
Fixing by steel springs.  
These devices are designed for modern control systems.  
For different options, see the "Light Control" section.

### Dimensions

20W: Ø115 x 115 x H.87mm, hole Ø95mm.

### Standard:

Quality marks: CE RoHS  
Standards: CEI EN 60598-1; CEI EN 60598-2-03.  
2014/30/EU, 2014/35/EU; ELR Ecodesign 2019/2015

## ACCESSORIES




**cod. REF020-S**  
(S) Shiny silver reflector



**cod. LEN020-L**  
(L) 60° lens



**cod. REF020-G**  
(G) Shiny gold reflector



**cod. KEM-90E**  
Emergency kit for LED equipment  
complete with battery for 3 hours duration.



**cod. LEN020-S**  
(S) 24° lens