


SGL LED - 2 x 12W




220V 240V	IP20 IP44	IK08		ECODESIGN COMPLIANT	CE RoHS	Ta -20° +45°C
--------------	--------------	------	--	------------------------	---------	------------------

Item.: **RC05124LB-927** (version on-off)
Item.: **RCD05124LB-927** (version DALI)

Recessed downlight LED, 220-240Vac, 24W,
2700K, CRI92, Standard 60°- Black reflector



Foro per
incasso 200 x 95 mm



Description

modular ceiling recessed system
Die-cast aluminum body.
Powder coating anti-yellowing stabilized against UV rays.
Reflectors in metallized PC.
Upper LED frosted screen in PC.
Compliant: EN 60598-1 and EN 60598-2-2.

Light source

COB LED with nominal efficiency up to 135 lumens/Watt.
Nominal flux: 3240 lm.
White color temperature: 2700 K.
Color rendering index: CRI92.
Lifetime: >50000h with L70.
Number of light sources: 2.
Output flux of the equipment: 2 x 1526 lm.

Electrical data

Driver power supply: input 220-240 Vac.
Average system power consumption: 24W.
Driver protections: Thermal, short circuit, overvoltage.
Driver connection: whit Internal terminal block.
Insulation class: II.
Functions: On-Off / DALI

Technical Description

Frame finish: Black.
Lamp protection: IP44.
Driver protection: IP20.
Mechanical resistance: IK08.
Quality marks: CE, RoHS..

Installation

Recessed installation.
Fixing by steel springs.
These devices are designed for modern control systems.
For different options, see the "Light Control" section.

Dimensions

Ø168x 88 x H.85mm, hole Ø75mm..

Standard:

Quality marks: CE RoHS
Standards: CEI EN 60598-1; CEI EN 60598-2-03.
2014/30/EU, 2014/35/EU; ELR Ecodesign 2019/2015

ACCESSORIES



cod. REF012-S
(S) Shiny silver reflector




cod. REF012-G
(G) Shiny gold reflector



cod. LEN012-S
(S) 24° lens



cod. LEN012-L
(L) 60° lens




cod. KEM-90E
Emergency kit for LED equipment
complete with battery for 3 hours duration.




SGL LED - 2 x 12W

220V 240V	IP20 IP44	IK08		ECODESIGN COMPLIANT	CE RoHS	Ta -20° +45°C
--------------	--------------	------	--	------------------------	---------	------------------

Item.: **RC05124LB-930** (version on-off)
Item.: **RCD05124LB-930** (version DALI)
Recessed On-Off downlightLED, 220-240Vac, 24W,
3000K, CRI92, Standard 60°- Black reflector



Foro per
incasso 200 x 95 mm



Description

modular ceiling recessed system
Die-cast aluminum body.
Powder coating anti-yellowing stabilized against UV rays.
Reflectors in metallized PC.
Upper LED frosted screen in PC.
Compliant: EN 60598-1 and EN 60598-2-2.

Light source

COB LED with nominal efficiency up to 135 lumens/Watt.
Nominal flux: 3240 lm.
White color temperature: 3000 K.
Color rendering index: CRI92.
Lifetime: >50000h with L70.
Number of light sources: 2.
Output flux of the equipment: 2 x 1590 lm.

Electrical data

Driver power supply: input 220-240 Vac.
Average system power consumption: 24W.
Driver protections: Thermal, short circuit, overvoltage.
Driver connection: whit Internal terminal block.
Insulation class: II.
Functions: On-Off / DALI

Technical Description

Frame finish: Black.
Lamp protection: IP44.
Driver protection: IP20.
Mechanical resistance: IK08.
Quality marks: CE, RoHS..

Installation

Recessed installation.
Fixing by steel springs.
These devices are designed for modern control systems.
For different options, see the "Light Control" section.

Dimensions

Ø168x 88 x H.85mm, hole Ø75mm..

Standard:

Quality marks: CE RoHS
Standards: CEI EN 60598-1; CEI EN 60598-2-03.
2014/30/EU, 2014/35/EU; ELR Ecodesign 2019/2015

ACCESSORIES



cod. REF012-S
(S) Shiny silver reflector




cod. REF012-G
(G) Shiny gold reflector



cod. LEN012-S
(S) 24° lens



cod. LEN012-L
(L) 60° lens



cod. KEM-90E
Emergency kit for LED equipment
complete with battery for 3 hours duration.


SGL LED - 2 x 12W

220V 240V	IP20 IP44	IK08		ECODESIGN COMPLIANT	CE RoHS	Ta -20° +45°C
--------------	--------------	------	--	------------------------	---------	------------------




Item.: **RC05124LB-940** (version on-off)

Item.: **RC05124LB-940** (version DALI)

Recessed On-Off downlightLED, 220-240Vac, 24W,
4000K, CRI92, Standard 60°- Black reflector



Foro per
incasso 200 x 95 mm



Description

modular ceiling recessed system
Die-cast aluminum body.
Powder coating anti-yellowing stabilized against UV rays.
Reflectors in metallized PC.
Upper LED frosted screen in PC.
Compliant: EN 60598-1 and EN 60598-2-2.

Light source

COB LED with nominal efficiency up to 135 lumens/Watt.
Nominal flux: 3240 lm.
White color temperature: 4000 K.
Color rendering index: CRI92.
Lifetime: >50000h with L70.
Number of light sources: 2.
Output flux of the equipment: 2 x 1611 lm.

Electrical data

Driver power supply: input 220-240 Vac.
Average system power consumption: 24W.
Driver protections: Thermal, short circuit, overvoltage.
Driver connection: whit Internal terminal block.
Insulation class: II.
Functions: On-Off / DALI

Technical Description

Frame finish: Black.
Lamp protection: IP44.
Driver protection: IP20.
Mechanical resistance: IK08.
Quality marks: CE, RoHS..

Installation

Recessed installation.
Fixing by steel springs.
These devices are designed for modern control systems.
For different options, see the "Light Control" section.

Dimensions

Ø168x 88 x H.85mm, hole Ø75mm..

Standard:

Quality marks: CE RoHS
Standards: CEI EN 60598-1; CEI EN 60598-2-03.
2014/30/EU, 2014/35/EU; ELR Ecodesign 2019/2015

ACCESSORIES



cod. REF012-S
(S) Shiny silver reflector




cod. REF012-G
(G) Shiny gold reflector



cod. LEN012-S
(S) 24° lens



cod. LEN012-L
(L) 60° lens



cod. KEM-90E
Emergency kit for LED equipment
complete with battery for 3 hours duration.


SGL LED - 2 x 12W

220V 240V	IP20 IP44	IK08		ECODESIGN COMPLIANT	CE	RoHS	Ta -20° +45°C
--------------	--------------	------	--	------------------------	----	------	------------------




Item.: RC05124LW-927 (version on-off)

Item.: RC05124LW-927 (version DALI)

Recessed On-Off downlightLED, 220-240Vac, 24W,
2700K, CRI92, Standard 60°- White reflector



Foro per
incasso 200 x 95 mm



Description

modular ceiling recessed system
Die-cast aluminum body.
Powder coating anti-yellowing stabilized against UV rays.
Reflectors in metallized PC.
Upper LED frosted screen in PC.
Compliant: EN 60598-1 and EN 60598-2-2.

Light source

COB LED with nominal efficiency up to 135 lumens/Watt.
Nominal flux: 3240 lm.
White color temperature: 2700 K.
Color rendering index: CRI92.
Lifetime: >50000h with L70.
Number of light sources: 2.
Output flux of the equipment: 2 x 1526 lm.

Electrical data

Driver power supply: input 220-240 Vac.
Average system power consumption: 24W.
Driver protections: Thermal, short circuit, overvoltage.
Driver connection: whit Internal terminal block.
Insulation class: II.
Functions: On-Off / DALI

Technical Description

Frame finish: White.
Lamp protection: IP44.
Driver protection: IP20.
Mechanical resistance: IK08.
Quality marks: CE, RoHS..

Installation

Recessed installation.
Fixing by steel springs.
These devices are designed for modern control systems.
For different options, see the "Light Control" section.

Dimensions

Ø168x 88 x H.85mm, hole Ø75mm.

Standard:

Quality marks: CE RoHS
Standards: CEI EN 60598-1; CEI EN 60598-2-03.
2014/30/EU, 2014/35/EU; ELR Ecodesign 2019/2015

ACCESSORIES



cod. REF012-S
(S) Shiny silver reflector




cod. REF012-G
(G) Shiny gold reflector



cod. LEN012-S
(S) 24° lens



cod. LEN012-L
(L) 60° lens



cod. KEM-90E
Emergency kit for LED equipment
complete with battery for 3 hours duration.


SGL LED - 2 x 12W

220V 240V	IP20 IP44	IK08		ECODESIGN COMPLIANT	CE	RoHS	Ta -20° +45°C
--------------	--------------	------	--	------------------------	----	------	------------------




Item.: **RC05124LW-930** (version on-off)

Item.: **RC05124LW-930** (version DALI)

Recessed On-Off downlightLED, 220-240Vac, 24W,
3000K, CRI92, Standard 60°- White reflector



Foro per
incasso 200 x 95 mm



Description

modular ceiling recessed system
Die-cast aluminum body.
Powder coating anti-yellowing stabilized against UV rays.
Reflectors in metallized PC.
Upper LED frosted screen in PC.
Compliant: EN 60598-1 and EN 60598-2-2.

Light source

COB LED with nominal efficiency up to 135 lumens/Watt.
Nominal flux: 3240 lm.
White color temperature: 3000 K.
Color rendering index: CRI92.
Lifetime: >50000h with L70.
Number of light sources: 2.
Output flux of the equipment: 2 x 1590 lm.

Electrical data

Driver power supply: input 220-240 Vac.
Average system power consumption: 24W.
Driver protections: Thermal, short circuit, overvoltage.
Driver connection: whit Internal terminal block.
Insulation class: II.
Functions: On-Off / DALI

Technical Description

Frame finish: White.
Lamp protection: IP44.
Driver protection: IP20.
Mechanical resistance: IK08.
Quality marks: CE, RoHS..

Installation

Recessed installation.
Fixing by steel springs.
These devices are designed for modern control systems.
For different options, see the "Light Control" section.

Dimensions

Ø168x 88 x H.85mm, hole Ø75mm.

Standard:

Quality marks: CE RoHS
Standards: CEI EN 60598-1; CEI EN 60598-2-03.
2014/30/EU, 2014/35/EU; ELR Ecodesign 2019/2015

ACCESSORIES



cod. REF012-S
(S) Shiny silver reflector




cod. REF012-G
(G) Shiny gold reflector



cod. LEN012-S
(S) 24° lens



cod. LEN012-L
(L) 60° lens



cod. KEM-90E
Emergency kit for LED equipment
complete with battery for 3 hours duration.


SGL LED - 2 x 12W

220V 240V	IP20 IP44	IK08		ECODESIGN COMPLIANT	CE	RoHS	Ta -20° +45°C
--------------	--------------	------	--	------------------------	----	------	------------------




Item.: RC05124LW-940 (version on-off)

Item.: RC05124LW-940 (version DALI)

Recessed On-Off downlightLED, 220-240Vac, 24W,
4000K, CRI92, Standard 60°- White reflector



Foro per
incasso 200 x 95 mm



Description

modular ceiling recessed system
Die-cast aluminum body.
Powder coating anti-yellowing stabilized against UV rays.
Reflectors in metallized PC.
Upper LED frosted screen in PC.
Compliant: EN 60598-1 and EN 60598-2-2.

Light source

COB LED with nominal efficiency up to 135 lumens/Watt.
Nominal flux: 3240 lm.
White color temperature: 4000 K.
Color rendering index: CRI92.
Lifetime: >50000h with L70.
Number of light sources: 2.
Output flux of the equipment: 2 x 1611 lm.

Electrical data

Driver power supply: input 220-240 Vac.
Average system power consumption: 24W.
Driver protections: Thermal, short circuit, overvoltage.
Driver connection: whit Internal terminal block.
Insulation class: II.
Functions: On-Off / DALI

Technical Description

Frame finish: White.
Lamp protection: IP44.
Driver protection: IP20.
Mechanical resistance: IK08.
Quality marks: CE, RoHS..

Installation

Recessed installation.
Fixing by steel springs.
These devices are designed for modern control systems.
For different options, see the "Light Control" section.

Dimensions

Ø168x 88 x H.85mm, hole Ø75mm.

Standard:

Quality marks: CE RoHS
Standards: CEI EN 60598-1; CEI EN 60598-2-03.
2014/30/EU, 2014/35/EU; ELR Ecodesign 2019/2015

ACCESSORIES



cod. REF012-S
(S) Shiny silver reflector




cod. REF012-G
(G) Shiny gold reflector



cod. LEN012-S
(S) 24° lens



cod. LEN012-L
(L) 60° lens



cod. KEM-90E
Emergency kit for LED equipment
complete with battery for 3 hours duration.