


CROWN-A 15W 3000K adjustable DALI


220V 240V	IP54 IP40	IK08		ECODESIGN COMPLIANT	CE	RoHS	Ta -20° +45°C
--------------	--------------	------	--	------------------------	----	------	------------------

cod.: RCD75H15-930

DALI Trimless recessed downlight 15W, 3000K, CRI>90, 36°
Beam angle, adjustable beam



Circular
CUT OUT Ø75 mm



Descriptions

CROWN-A LED is a trimless recessed ceiling fixture, adjustable beam and DALI dimmable. Its light beam can be rotated vertically by 30° with respect to the installation plane and rotated horizontally by 355° to meet installation needs. Bridgelux LED COB light source with high color rendering and excellent efficiency class.

Light source

LED: COB LED

Energy classification according to Ecodesign directive ELR 2019/2015: **D**

Color temperature: 3000K

Color rendering index: CRI90

Life time: L80 B10 60000 h

Light source quantity: 1

Nominal flux: 1377.6 lm

Efficiency LED: 91.84 lm/W

Output flux: 1109 lm

Output efficiency: 73.93 lm/W

Beam angle: 36°

Photobiological risk class: "GR0" Exempt

Electrical data

Driver: C.C. DALI Driver included (Made in Italy)

Input driver: 220-240 Vac

Power consumption: 15W

PF: 0.90

Driver protections: Thermal, short circuit, overvoltage

Insulation class: II

Functions: DALI dim. / ON-Off

Technical Description

Adjustable, extractable, tilting recessed fixture for LED source with high color rendering index (CRI>90). Passive heat dispersion system. Frame and main body in die-cast aluminum. Body orientation with manual maneuvering device: 90° - rotation on the axis 350°. Reflector with high efficiency optics in

1090 aluminum - 36° opening. Closing ring of the lamp body in die-cast

aluminum. Transparent tempered protective glass. On-off

flicker-FREE power supply, (Flickering classification 0.5% - NO RISK) supplied

connected to the device.

Lamp protection: IP54

Driver: IP40

Resistance: IK08

N.W.: 1.4Kg

CEI EN 60598-1; CEI EN 60598-2-03.

Standard:

2014/30/EU, 2014/35/EU; CEI EN 60598-1; CEI EN 60598-1/A1; CEI EN 60598-2-1, EN61000-3-2; EN61000-3-3; EN61000-4-3; EN61000-4-8; EN61547:2009; 2015/863/UE; EN62493:2015; EN55015:2019/A1:2020; EN 62471, 2009/125/CE, 874/2012/CE; Ecodesign ELR 2019/2015.