

SPENK-2 LED 90°-5W



220V 240V	IP65	IK05		ECODESIGN COMPLIANT	CE	RoHS	Ta -40° +45°C
--------------	------	------	--	------------------------	----	------	------------------

item: **SLO3HM05-830**


SPOT LED IP65, 230Vdc, 3000K, 90°
5W, on-off, LED



Antracite RAL7015



UNITÀ: mm



Product description

SPENK-2 IP65 is the new version of the garden spotlight with an interchangeable LED light source, ideal for illuminating small trees, bushes, rock gardens, or small outdoor and indoor structures. SPENK-2 comes with a power cord with a plug, which is not only convenient for the user but also complies with the latest standards for portable garden fixtures. The fixture is very easy to secure to the ground using its "spike"; simply insert it into the ground. A replaceable light source and IP65 sealing are further advantages.

Light source

Interchangeable 220V LED module
White LED energy rating: E (Ecodesign ELR 2019/2015)
White LED color temperature: 3000K
Color rendering index: CRI>80
Estimated life: L80 B10 60,000 hours
Number of LEDs: 1
Full-On Emission: 500 lm
Photobiological risk class: "GR0" Exempt

Electrical data

Internal driver: DC-DC (MTBF: 65,000h)
Power supply: 220-240 VAC
Full-on consumption: 5W
Connections: Cable
Insulation class: II
Functions: Dimmable / color mixing

Mechanical data

Body finish: RAL7015 anthracite
Aluminum body with anti-corrosion treatment.
Adjustable steel bracket.
Protection: IP65
Mechanical resistance: IK05
Marking: CE RhOS
CEI EN 60598-1; CEI EN 60598-1/A1; CEI EN 60598-2-1.

Applied rules

Standard: 2014/30/EU, 2014/35/EU
CEI EN 60598-1; CEI EN 60598-1/A1; CEI EN 60598-2-1,
EN61000-3-2; EN61000-3-3; EN61000-4-3; EN61000-4-8
EN61547:2009; 2015/863/UE
EN62493:2015; EN55015:2019/A1:2020
EN 62471, 2009/125/CE, 874/2012/CE,
Ecodesign ELR 2019/2015