



Professional Aluminium LED Profile BAR


S22 square

Surface / recessed



S22 is an extremely versatile anodized aluminum profile with compact dimensions. It can be used as a surface or recessed mounting. Completely illuminating its T-shaped diffuser. It features a retractable clip for fixing. S22 allows you to create a line of light that stylishly highlights any surrounding space. Custom profiles are available, complete with internal LED strip, power cable, and mounting accessories.

unit.: mm



THE STANDARD CONFIGURATION:

- L. 2 m Aluminium BAR with opal diffuser and end cap
- L. 2 m LED Line
- Nr. 2 pcs mounting clips



Technical Data of LED BAR with LED linear module inside:

cod.	CCT	VOLT	WATT	lm/m	length
BL-06-927	2700K	24V	20W	562lm	2 mt
BL-06-927	2700K	24V	48W	1350lm	2 mt



Light source data


Light source: SMD LED 2835 module 20W/m
Lumens per meter: 2184 lm/m
color temperature: 2700K
Light output: 91 lm/W
Color rendering index: CRI>90
Beam angle: 120°
Energy class: F (Ecodesign ELR 2019/2015)
Flow maintenance: L80 B10 60000 h
Photobiological classification: Risk "0" Exempt

Light source Electrical data

Input: 24 Vdc
Power consumption: 24 W/m
Connection: Double wire soldered on polarized pads
Insulation class: III Dimmable: by accessories

Light source Mechanical data

Use: Indoor or outdoor based on the profile that is used
Maximum length: 5000mm W: 10mm H: 2.5mm
Insulated copper board: White color
Cutttable length: 50 mm
Fixing: 3M double-sided adhesive on the back side



OPTIONAL ACCESSORIES



cod. PAT2213-G (silver)
end cap kit



cod. PAC2213
mounting clips



cod. PELG-150-24-DA
DALI driver 150W - 24V - IP67
(one DALI power supply is matched
with 6 mt. LED Line)